

Prism

BRIDGING THE GAP BETWEEN SDI & IP TRANSITION

- New platform - MPi
 - 3RU Half rack platform with 9 inch HD display and touch panel
 - Simplified user interface – Web browser operation
 - Designed to be flexible to the standards
- Feature sets
 - ST2022-6, IEEE1588/ST2059 at first
 - Specialized measurements for IP/SDI hybrid environment
 - Picture, waveform, audio ... for conformance testing
 - New display layout for intuitive operation



Prism

MEDIA PLATFORM - FRONT

Shorter Depth:
11.7 in
(WFM8k: 18.2in)


Touch Panel
Operation

Quad/Full/Entire
Tile layout



MPI

MEDIA PLATFORM - REAR



MPI

MEDIA PLATFORM - REAR

- 2x 10GbE SFP+
 - 1x 10GbE enabled
 - ST2022-6, PTP (ST2059 profile)
- 4x 12G capable SDI input
 - HD/3G single link SDI with Audio
 - 1080i50/59, 1080p50/59, 720p50/59
- 2x SDI SFP+
 - Loop through output (TBD)
 - Optical SDI input (TBD)
- AUX SDI output
 - ST2022-6 to SDI conversion output
- LTC, GPI
 - Not enabled
- External Reference
 - BB only
- 2x 1GbE management port
 - Remote operation by VNC
- 2x Display Port
 - Mirror mode
- 4x USB
 - Keyboard & Mouse, USB memory
- Audio output
 - Headphone



Operation option

MEDIA PLATFORM

- Touch panel
 - In front of you
- Key board and Mouse
 - A few feet away, In editing room
- External monitor with touch panel
 - In machine room, No keyboard tray needed
- Remote operation
 - From your desk
 - Install the box at remote location



以上内容仅为本文档的试下载部分，为可阅读页数的一半内容。如要下载或阅读全文，请访问：<https://d.book118.com/475041200131011101>